



**Gruber
Power
Services**

Premium High Rate Battery Series

Sealed Lead Acid Battery

6 Volt - 12 Amp Hour

GPS12-6S



Features

- Lead alloy with low calcium minimizes gassing and extends life of grid.
- Through unique active material recipes, plates after undergoing curing and tank formation provide outstanding energy density and ensure the quality of the battery.
- Using brass coated lead alloy battery terminals minimizes impedance of connecting cells inside.
- Case made of ABS resin and cells kept under internal pressure protects from outer shock or impact.
- Micro-porous AGM separator completely absorbs and retains electrolyte under the pressured cell design.
- Electrolyte sufficiently serves for electrochemical reactions in battery but never spills.
- Battery cases are sealed in epoxy and cells are covered with vents to avoid cell contamination with the atmosphere and serve for internal oxygen reaction.
- With very little gas evolution, the water loss is minimized and service life is extended. Excess pressure and gas will be released which ensures safety.
- Vent design is certificated by UL.

Applications

- UPS
- Communications
- Lighting
- Security & Alarm
- Medical Equipment
- Remote Monitoring
- Solar Energy Station
- Golf Carts
- Wheelchairs
- Motorcycles
- Scooters
- Riding Mowers
- Snowmobiles
- Water Sports

Transport

- Air transportation complies with IATA/ICAO special provision A67.
- Surface transport classification as non-hazardous material as related to DOT-49CFR173.159.
- Water transport classification as non-hazardous material per IMDG Amendment 27.

